

HAI TECHNICAL UPDATES "Model 1106 Version 2.2 Update "

This version of the HAI PC Access Software supports OmniLT, Omni, Omni II, OmniPro, and OmniPro II systems.

ADD THIS DOCUMENT TO YOUR MODEL 1106 PC ACCESS MANUAL

Version 2.2 of the Model 1106W PC Access Software adds support for the ALC 4-Button Scene Switch Module and ALC switch press event programs.

INSTALLATION

To install this software, run the PC Access setup program as follows:

1. Insert the 1106W PC Access CD into your CD-ROM drive.
2. Select the **Run** command from the **Start** menu.
3. Type <drive>:setup

For example, if the Setup disk is in drive D, type "d:setup".

4. Follow the instructions provided on the screen.

When updating from the DOS version of PC Access, copy all account files with the extension of ".pca" and the configuration file "PCA.cfg" from the existing PC Access directory to the PC Access folder "C:\Program files\HAI\PC Access". This will ensure that the PC Access software will access your existing account files using your current security stamp and password.

STARTING THE PROGRAM

To start the PC Access software, click the **Start** button, point to **Programs**, point to **HAI**, point to **PC Access**, then click **PC Access 2.2**.

If you experience any difficulties, you may call HAI during regular business hours for assistance.